

Provided by Xpert Survey Equipment
Click Spectra Precision Focus 30 for Product Info and Updated Pricing



FOCUS 30 Total Station



Improve your Field Efficiency
with a Robotic Total Station



FLEXIB
RELIABL
PRODUCTIVE

FOCUS[®]

FOCUS 30



Featuring World Class Spectra Precision Field Software

Introducing the powerful Spectra Precision® FOCUS 30 Total Station. This fully robotic motorized solution provides improved speed, accuracy and precision in measurement. A robotic instrument moves the power of the observer from the instrument to the range pole improving the quality of your work.

all robotic instruments include:

- Motorized drive system at the instrument
- A tracking sensor to track the range pole and prism
- A communication connection between the instrument and range pole and



StepDrive

The speed of observation and precise positioning of the FOCUS 30 robotic total station is provided by patented StepDrive™ technology. StepDrive controls the horizontal and vertical motion of the motors, so there is no need for traditional motion locks. Using the motorized drives it is possible to precisely turn to, and repeat angle measurements. This results in quick and reliable measurements which substantially increases your staking productivity.

LocknGo

The Robotic and LockNGo™ FOCUS 30 models include a tracking sensor that uses LockNGo technology enabling the instrument to constantly lock onto the prism. The benefit of LockNGo technology is the ability to follow the prism at all times and reduces downtime from not having to re-point the instrument on every observation.

Communication Link

To maintain contact between the FOCUS 30 instrument and the remote observer with the range pole and prism, the robotic solution must include a communication link. The FOCUS 30 uses an integrated 2.4 GHz radio modem as does the Spectra Precision Ranger™ 3 data collector. The 2.4 GHz radio modems provide interference free robotic data communications. Once your robotic communications have been established you can control all the functions of the FOCUS 30 from the range pole as you move through the job site making measurements. This makes it possible for a single surveyor to perform high accuracy stakeout, layout or topographic surveys by themselves. From high-order control surveys to topographic data collection or fast-paced construction layout, you can rely on a FOCUS 30, even in harsh outdoor conditions.

FOCUS 30 and Survey Pro

Combined with Spectra Precision Survey Pro™ field software, providing you with world class software solutions for any surveying situation. An example of these features includes a unique robotic software technology that can be used when associating the FOCUS 30 with a low-cost GPS receiver and Survey Pro software. This combination of technologies allows the user to take full advantage of the Spectra Precision GeoLock™ technology to keep locked on target.

The Spectra Precision GeoLock technology

Offered in Survey Pro this technique allows a robotic total station to perform an aided search for an optical target using an initial GPS position. The remote instrument can then be directed towards the robotic roving operator using the GPS position and a subsequent search is quickly performed to re-acquire the target at the robotic rover. This technique greatly reduces wasted time, improving your field work efficiency.

FOCUS 30 and Layout Pro

Spectra Precision Layout Pro™ software and the FOCUS 30 together offer the convenience of carrying, managing, editing, and laying out your job site blueprint. This combination is a critical tool in the field of construction layout and is designed to make the layout process more productive, accurate and reliable. For example, use Layout Pro to guide the layout of the major points, add string dimensions on the print, as well as calculate diagonals and angles.

Features

- Survey Pro™ and Layout Pro™ software
- GeoLock™ GPS assist technology
- 2", 3", and 5" angle accuracy
- StepDrive™ motion technology
- LockNGo™ advanced tracking technology
- Windows CE Touchscreen
- Ultra lightweight at only 5 kg (11 lb)
- 2.4 GHz interference-free radio
- Spectra Precision Ranger 3XR data collector



The FOCUS 30 solution is best described as Simply Powerful. Packaged in a modern, sleek, and streamlined design, it is easy-to-use, affordable, and tough.

FOCUS 30 Total Station

PerFORManCe

angle measurement

Accuracy

(Standard deviation

based on ISO 17123-3) 2" (0.6 mgon),
3" (1.0 mgon), or 5" (1.5 mgon)

Angle reading (least count display)

Standard1" (0.1 mgon)

Tracking2" (0.5 mgon)

Distance measurement†

Accuracy to Prism

(Standard deviation based on ISO 17123-4)

Standard 2 mm + 2 ppm (0.007 ft + 2 ppm)

Tracking 5 mm + 2 ppm (0.016 ft + 2 ppm)

Accuracy Reflectorless Mode

Standard

<300 m (984 ft) 3 mm + 2 ppm (0.01 ft + 2 ppm)

Standard

>300 m (984 ft) 5 mm + 2 ppm (0.016 ft + 2 ppm)

Tracking 10 mm + 2 ppm (0.033 ft + 2 ppm)

Measuring time

Prism Standard 2.4 sec.

Prism Tracking 0.5 sec.

Reflectorless Standard 3–15 sec.

Reflectorless Tracking 0.7 sec.

Range Prism Mode

1 prism 4000 m (13,123 ft)

3 prisms 7000 m (22,966 ft)

Foil Reflector 60 mm 300 m (984 ft)

Range Reflectorless Mode

Good‡ Normal‡ Difficul‡

KG‡ (18%) 400 m 350 m 300 m

(1,312 ft) (1,148ft) (984 ft)

KGC (90%) 800 m 600 m 400 m

(2,625 ft) (1,969 ft) (1,312 ft)

Foil Reflector 1,000 m 1,000 m 800 m

60 mm (3,280 ft) (3,280 ft) (2,625 ft)

Shortest possible range 1.5 m (4.9 ft)

automatic level compensator

Type dual-axis

Accuracy 0.5" (0.15 mgon)

Working Range ±5.5" (±100 mgon)

eDm SPECIFICATIOnS

eDm Laser and Principle

Light source Laser Diode 660 nm

Principle Phase Shift

eDm Beam divergence

Horizontal 4 cm/100 m (0.13 ft/328 ft)

Vertical 3 cm/100 m (0.10 ft/328 ft)

Atmospheric Correction -150 ppm to 160 ppm
continuously

General SPECIFICATIOnS

Coarse Leveling

Electronic coarse leveling range ±3" (±3.3 gon)

Circular level in tribrach 8/2 mm (8/0.007 ft)

Drives

Drive system Spectra Precision StepDrive® system

Rotation time maximum 90°/sec (100 gon/sec)

Rotation time Face 1 to Face 2 3.7 sec.

Positioning time 180° (200 gon) 3.5 sec.
Clamps and slow motions StepDrive driven,
endless fine adjustment

Centering

Centering system3-pin

Plummet Built-in optical plummet

Magnification 2.4 x

Focusing distance 0.5 m to ∞ (1.6 ft to ∞)

Telescope

Magnification 31x

Aperture 50 mm (1.96 in)

Field of view 1°30'

Focusing distance 1.5 m to ∞ (4.9 ft to ∞)

Illuminated crosshair Standard

Tracklight built in Standard

Trunnion axis height 196 mm (7.71 in)

environmental

Operating temperature -20 °C to +50 °C

(-4 °F to +122 °F)

Dust and water proofing IP55

Power supply

Internal battery Li-Ion, 11.1 V/5.0 Ah

Operating time with one internal battery Approx. 6 hours

Communications

External foot connector USB cable connection

and external power supply

Wireless communication Bluetooth

Weight

Instrument 5.0 kg (11.0 lb)

Tribrach 0.7 kg (1.54 lb)

Internal battery 0.3 kg (0.66 lb)

ROBOTIC SPECIFICATIOn

robotic Operation 1

Maximum Robotic Range 300 m to 800 m

(984 ft to 2,625 ft)

Point precision at 200 m (656 ft) <2 mm (0.007 ft)

Maximum Search Distance 300 m to 800 m

(984 ft to 2,625 ft)

Search Time (typical) 2–10 sec.

Communications

internal/external 2.4 GHz, frequency hopping,

spread spectrum

GPS Search GeoLock

GPS Search GeoLock 360° (400 gon)

Range Full robotic operation range

DaTa COLLECTIOn

Control Units fixed on alidade

Face 1

Display 3.5" TFT color touch screen,

320x240 Pixel, backlight

Keyboard Alphanumeric keypad

Memory (data storage) 128 MB RAM, 128 MB Flash

Field App. Software Survey Pro and Layout Pro

Face 2

Display 6 lines, monochrome, 96x49 Pixel, backlight

Keyboard 4 keys

Instrument Software Functions Change Face

Radio and Instrument Settings,

Measurement Value Display, Leveling



CerTIFICATIOn

Class B Part 15 FCC certification, CE Mark approval.

C-Tick.

Laser safety IEC 60825-1 am2:2007

Prism Mode: Class 1

Reflectorless/Laser Pointer: Class 3R laser

Bluetooth type approvals are country specific.

- 1 Standard clear: No haze, overcast or moderate sunlight with very light heat shimmer. Range and accuracy are dependent on atmospheric conditions, size of prism and background radiation.
- 2 Kodak Gray Card, Catalog number E1527795.
- 3 Good conditions (good visibility, overcast, twilight, underground, low ambient light)
- 4 Normal conditions (normal visibility, object in the shadow, moderate ambient light).
- 5 Difficult conditions (haze, object in direct sunlight, high ambient light).
- 6 Spectra Precision GeoLock is available on data collectors after station setup.



Contact Information:

amerlCaS

Spectra Precision Division
10368 Westmoor Drive
Westminster, CO 80021 • USA
+1-720-587-4700 Phone
888-477-7516 (Toll Free in USA)

eUrOpE, mIDDLe eaST and aFRICa

Spectra Precision Division
Rue Thomas Edison
ZAC de la Fleuriaye – BP 60433
44474 Carquefou (Nantes) • FRANCE
+33-(0)2-28-09-38-00 Phone

aSIa-PaCIFIC

Spectra Precision Division
80 Marine Parade Road
#22-06, Parkway Parade
Singapore 449269 • SINGAPORE
+65-6348-2212 Phone



www.spectraprecision.com

Please visit www.spectraprecision.com for the latest product information and to locate your nearest distributor. Specifications and descriptions are subject to change without notice.

© 2010–2013, Trimble Navigation Limited. All rights reserved. Spectra Precision is a Division of Trimble Navigation Limited. Spectra Precision and the Spectra Precision logo are trademarks of Trimble Navigation Limited or its subsidiaries. FOCUS is a trademark of Spectra Precision. StepDrive is an unregistered trademark of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks is under license. Windows Mobile is a trademark of Microsoft Corporation, registered in the United States and/or other countries. All other trademarks are the property of their respective owners. PN 022487-168F (05/13)

SCAN THIS CODE FOR MORE INFORMATION

